

LIS007854812B2

(12) United States Patent

Harman, Jr.

(10) Patent No.: US 7,854,812 B2 (45) Date of Patent: Dec. 21, 2010

(54)	PROCESS FOR FINISHING WALLBOARD
	IOINTS

(76) Inventor: George William Harman, Jr., 13709 E.

Devonfield Dr., Baldwin, MD (US)

21013

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 175 days.

(21) Appl. No.: 12/220,822

(22) Filed: Jul. 29, 2008

(65) **Prior Publication Data**

US 2009/0032197 A1 Feb. 5, 2009

Related U.S. Application Data

- (60) Provisional application No. 60/963,141, filed on Aug. 2, 2007.
- (51) **Int. Cl. B44C** 7/04 (2006.01)
- (52) **U.S. Cl.** **156/71**; 156/574; 156/575; 156/577; 156/579

See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

3,109,207	Α	*	11/1963	Cooper	52/255
4,313,991	Α		2/1982	Lamb	
4,336,097	Α	*	6/1982	Van Kampen et al	156/527
4,486,263	Α	*	12/1984	Monzo Gomez	156/523

5,079,042	A	1/1992	Frings	
5,313,755	A	5/1994	Koenig, Jr.	
5,381,942	A *	1/1995	Lin	225/56
5,604,001	A	2/1997	Schold	
6,148,573	A	11/2000	Smythe, Jr.	
6,223,486	B1 *	5/2001	Dunham	52/254
2003/0024188	A1	2/2003	Smythe	
2003/0033770	A1	2/2003	Harel	
2004/0093816	A1	5/2004	Smythe	
2005/0028483	A1	2/2005	Smythe	
2006/0101746	A1	5/2006	Smythe	

OTHER PUBLICATIONS

3M Company website (www.3m.com) one page.

* cited by examiner

Primary Examiner—Kahnh Nguyen Assistant Examiner—Margaret Squalls (74) Attorney, Agent, or Firm—John E. Simms, Jr.

(57) ABSTRACT

A joint compound guide bead dispenser, for finishing wall-board joints and a process for finishing wallboard joints. The guide bead dispenser includes a housing containing an adhesive coated cord wound on a rotatably mounted spool. The housing has an opening through which the cord passes and a roller rotatably mounted proximate to the opening. A cutting blade is mounted on the housing proximate to the opening. A length of cord may be payed out through the opening. The cord may be adhered to wallboard, proximate to a joint, by applying pressure with the roller and cut to selected length. Joint compound may be applied to cover the joint and smoothed to a uniform feathered finish by resting a straight edged knife on the wallboard and on the guide bead while moving the knife in a joint compound applying stroke.

4 Claims, 3 Drawing Sheets

